



"Caterpillar" No. 28 Ripper

SPECIFICATIONS ON OTHER SIDE

SPECIFICATIONS

"CATERPILLAR" NO. 28 RIPPER

| | |
|---|--------------------------|
| Model | No. 28 |
| Type Controls, required on tractor | Rear cable control |
| Number of lines required | One |
| Over-all Dimensions: | |
| Length | 20' |
| Width | 8' - 8" |
| Height (Loaded for shipment) | 7' - 8½" |
| Wheels: | |
| Type | Steel drum |
| Size | 40" x 10" |
| Gauge—(Center to center) | 62" |
| Type of wheel bearings | Tapered roller |
| Axles | Heat-treated steel |
| Sheaves: | |
| Diameter | 9¾" |
| Type bearings | Roller |
| Grease fittings | Alemite |
| General Specifications: | |
| Max. ground clearance—(Teeth) | 11" |
| Max. depth of penetration | 30" |
| Number of teeth | 3 |
| Type of tooth | Detachable |
| Tip Replaceable material | Heat-treated alloy steel |
| Tooth spacing—(Center to center) | 46" |
| Distance between outside teeth—(Center to center) | 92" |
| Shank size | 3" x 10" |
| Length of ½" cable required | 80' |
| Weight: Shipping (approx.) | 13,000 lbs. |

Removable cover plates are provided in frame to permit filling with sand which will increase operating weight approximately 2,200 lbs.

The No. 28 Ripper may be used with one or two D8 tractors.

CATERPILLAR TRACTOR CO., . . . Peoria, Illinois

DIESEL ENGINES — TRACTORS — MOTOR GRADERS — EARTHMOVING EQUIPMENT